



Constituent Material	PVC, Exterior Grade Rigid only	PVC, Exterior Grade Rigid only	
Section Width (W)	18 inches	457 mm	
Section Depth (D)	10 inches	254 mm	
Section Thickness (T)	.350 inches	8.89 mm	
Weight	7.1 lbs/lineal foot	10.30 kg/lineal meter	
Moment of Inertia	129.6 in ⁴ /ft	17,698 cm ⁴ /m	
Section Modulus	24.9 in ³ /ft	1,339 cm ³ /m	
Ultimate Moment	13,487 ft-lbs/ft	6,194 kg-m/m	
Allowable Moment	6,743 ft-lbs/ft	3,097 kg-m/m	
Tensile Strength	ASTM-D638	6,500 lbs/in ²	44.8 Mpa
Flexural Strength	ASTM-D790	11,140 Psi	78.0 Mpa
Modulus of Elasticity	ASTM-D790	380,000 Psi	2,620 Mpa
Notched Izod Impact	ASTM-D256	13.75 lbs/in	2.46 kg/cm
Heat Deflection Temperature	ASTM-D648	158 degrees F	70 degrees C

- Available Colors** Tidewall Vinyl Sheet Piling comes in a standard color of light gray, but it is also available in clay, slate and other custom colors upon request.
- UV Protection** All Tidewall Products are produced from highly weatherable, UV-stabilized rigid PVC.
- Lifetime Warranty** Tidewall Vinyl Sheet Piling products are covered by a transferable 60 year Limited Warranty that protects against manufacturing defects.

The information provided are nominal values and are believed to be accurate. To insure that you select the proper Tidewall Vinyl Sheet Piling product for your particular application, Tidewall recommends that you consult with a qualified local engineer and/or contractor. Tidewall makes no warranty of any kind as to the suitability of Tidewall Vinyl Sheet Pile for a particular application, or the results obtained therefrom. Tidewall Vinyl Sheet Piling is engineered for the sheet piling construction industry according to United States Army Corps of Engineers design guidelines and tested to ASTM material specifications.